

## SZ series 7mm LOW IMPEDANCE

- Low impedance at 100kHz operating temperature range -55~105°C
- Load life:105°C 1000hours
- High Quality

### ■SPECIFICATIONS

Item	Performance Characteristics																											
Operating Temperature Range	-55~105°C																											
Rated Voltage Range	6.3~50V																											
Capacitance Range	1~470uF																											
Capacitance Tolerance	±20% at 120Hz,20°C																											
Leakage Current (MAX)	I≤0.01CV or 3uA whichever is greater. ( after 2 minutes )																											
Dissipation Factor (tan δ)	When nominal capacitance is over 1000uF,tan δ shall be added 0.02 to the listed value with increase of every 1000uF. <table border="1"> <tr> <th>Rated voltage(V)</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> </tr> <tr> <th>Tan δ</th> <td>0.22</td> <td>0.19</td> <td>0.16</td> <td>0.16</td> <td>0.14</td> <td>0.12</td> </tr> </table> MAX ( 20°C 120Hz )							Rated voltage(V)	6.3	10	16	25	35	50	Tan δ	0.22	0.19	0.16	0.16	0.14	0.12							
Rated voltage(V)	6.3	10	16	25	35	50																						
Tan δ	0.22	0.19	0.16	0.16	0.14	0.12																						
Low Temperature Stability Impedance Ratio	Measurement frequency:120Hz <table border="1"> <tr> <th>Rated voltage(V)</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> </tr> <tr> <th>Impedance ratio Z(-25°C) / Z(+20°C)</th> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> </tr> <tr> <th>ZT/Z20 ( MAX ) Z(-40°C) / Z(+20°C)</th> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> </tr> </table>							Rated voltage(V)	6.3	10	16	25	35	50	Impedance ratio Z(-25°C) / Z(+20°C)	2	2	2	2	2	2	ZT/Z20 ( MAX ) Z(-40°C) / Z(+20°C)	3	3	3	3	3	3
Rated voltage(V)	6.3	10	16	25	35	50																						
Impedance ratio Z(-25°C) / Z(+20°C)	2	2	2	2	2	2																						
ZT/Z20 ( MAX ) Z(-40°C) / Z(+20°C)	3	3	3	3	3	3																						
Load Life	After life test at conditions stated in the table below 1000hrs 105°C, the capacitors shall meet the following requirement. <table border="1"> <tr> <td>Leakage Current</td> <td>Not more than the specified value</td> </tr> <tr> <td>Capacitance Change</td> <td>Within ±20% of initial value</td> </tr> <tr> <td>Dissipation Factor</td> <td>Not more than 200% of the specified value</td> </tr> </table>							Leakage Current	Not more than the specified value	Capacitance Change	Within ±20% of initial value	Dissipation Factor	Not more than 200% of the specified value															
Leakage Current	Not more than the specified value																											
Capacitance Change	Within ±20% of initial value																											
Dissipation Factor	Not more than 200% of the specified value																											
Shelf Life	After leaving capacitors under no load at 105°C for 1000hours and applying voltage according to JIS C-5102 4-3, they meet the specified value for load life characteristics listed above.																											
Standard	According to JIS C-5141																											

### ■MULTIPLIER FOR RIPPLE CURRENT


#### Frequency coefficient

Cap(uF) \ Frequency(Hz)	60(50)	120	400	1k	10k	50~100k
6.8~10	0.47	0.59	0.76	0.85	0.97	1.00
10≤cap≤100	0.52	0.65	0.80	0.89	0.97	1.00
100≤cap≤1000	0.58	0.72	0.84	0.90	0.98	1.00

Temperature	60°C	70°C	85°C	105°C
Coefficient	1.8	1.5	1.3	1.0

**SZ** series 7mm LOW IMPEDANCE

## DIMENSIONS(mm)



ΦD	4	5	6.3	8
Φd	0.45		0.5	
F	1.5	2.0	2.5	3.5
α	1.0			

## STANDARD SIZE PERMISSIBLE RIPPLE CURRENT

Size ΦD×L(mm) Ripple Current(mA 105°C, 120Hz)r.m.s

Cap(uF)	W.V	6.3			10			16		
		SIZE	Ripple	Impedance	SIZE	Ripple	Impedance	SIZE	Ripple	Impedance
10								4x7	60	2.1
22					4x7	70	3.2	4x7 5x7	85 100	2.0 1.8
33	5x7	100	1.72	5x7	105	1.7	6.3x7	140	1.3	
47	5x7	100	1.72	5x7	120	1.5	4x7 5x7 6.3x7	100 125 150	1.8 1.6 1.2	
68	6.3x7	150	0.85	6.3x7	160	0.82	8x7	180	0.55	
100	5x7 6.3x7	145 150	0.88 0.85	5x7 6.3x7	160 190	0.82 0.54	6.3x7 8x7	200 210	0.50 0.45	
120	6.3x7	160	0.72	6.3x7	200	0.49	8x7	340	0.37	
150	6.3x7	170	0.62	8x7	220	0.45	8x7	360	0.33	
180	8x7	180	0.58	8x7	240	0.43	8x7	390	0.31	
220	6.3x7 8x7	175 200	0.60 0.52	6.3x7 8x7	240 280	0.43 0.38	8x7	420	0.28	
330	8x7	320	0.38	8x7	290	0.35				
470				8x7	300	0.25				

Size ΦD×L(mm) Ripple Current(mA 105°C, 120Hz)r.m.s

Cap(uF)	W.V	25			35			50		
		SIZE	Ripple	Impedance	SIZE	Ripple	Impedance	SIZE	Ripple	Impedance
1								4x7	51	7.5
4.7								5x7	140	1.4
6.8					4x7	75	3.2			
10	4x7	65	3.1	5x7	120	1.65	5x7	150	1.3	
22	5x7	105	1.8	6.3x7	165	0.78				
33	6.3x7	160	0.8	8x7	205	0.49				
47	5x7 8x7	130 205	1.10 0.55	6.3x7 8x7	215 248	0.52 0.48				
68	8x7	205	0.50							
100	6.3x7 8x7	240 252	0.36 0.34							
150	8x7	330	0.38							

※以上最大体积为标准尺寸，其他为体积缩小品，寿命相应缩短